

# CLICKSYS™

Quick Engineering Guide

## Maximum Span Chart (in)



Bright Thinking in Solar

© 2009 by Unirac, Inc. All rights reserved.

Pub 090518-1qe, April 2009

<i>Basic Wind Speed (mph)</i>	<i>0 psf Snow</i>	<i>0 - 15 psf Snow</i>	<i>21-40 psf Snow</i>
85 mph or Less	54"	48"	40"
86 - 90 mph	52"	48"	40"
91 - 110 mph	47"*	44"	38"
111 - 150 mph	38"	38"	32"

**\* 48" is allowable if beam is supported by 3 or more connections**

**See reverse for limitations**

**[www.clicksys-beam.com](http://www.clicksys-beam.com)**

## CLICKSYS™ Quick Engineering Guide Limitations

- Flush roof installations only
- Module must not be placed in roof overhang zone
- Roof slope must be 0 - 45 degrees (0/12 - 12/12 pitch)
- Installation must have at least 4 modules grouped together
- Module dimensions must be less than 40" x 65"
- Surrounding ground area must not slope more than 10 degrees
- Location must fall into Exposure Category B or C
- Building height must be less than or equal to 30'0"

*Please refer to Unirac Technical Support for more information on roof zones*

- Span for Roof Zone 2 = 1/2 Max Span
- Span for Roof Zone 3 = 1/3 Max Span
- Max Cantilever = 1/3 Max Span

***For installations that do not comply with the limitations above, please refer to [www.clicksys-beam.com](http://www.clicksys-beam.com) for a full engineering design guide.***